

DANUSER T3™ HYDRAULIC POST DRIVER

Designed for high-output fencing work, the T3 Hydraulic Driver delivers up to 2,000 lb of force and six strikes per second, driving posts of up to 3 inches O.D. with precision and control.



Type: Hydraulic Post Driver

Brand: Danuser

Model Number: PDT3DS



TECHNICAL SPECIFICATIONS *(Provided by Danuser Manufacturing Company)*

Operating Pressure	10–30 GPM Hydraulic Flow
Operating Range	1,500–3,500 PSI
Impact Force	Up to 2,000 lb
Strikes per Second	Up to 6
Compatible Post Sizes	T-Posts, Round Pipe, and Square Tubes up to 3" O.D.
Construction	Fully Enclosed Hammer System with Reinforced Steel Housing
Mounting Options	Universal Skid-Steer, Euro/Global, John Deere 400/500 Series, Mini Skid, Tractor Loader, Excavator
Attachment Type	Hydraulic Quick-Attach Mount
Driver Weight	300 lbs [136 kg]
Hydraulic Hose Length	78" [1.98 m]
Hydraulic Fittings	½" Flat Face Couplers
Compatible Machines	Skid Steers, Mini Skids, Loaders, Tractors, and Excavators
Compatible Post Sizes	Round Pipe up to 2-3/8" OD, T-Posts, Ground Rods, Concrete Pins

WHY CHOOSE THIS MODEL?



Reliable hydraulic performance for high-volume fencing and containment projects.



Drives posts up to 3" O.D. faster than manual or gas-powered drivers.



Supported by SONCO with nationwide stock and expert guidance.



U.S.-built and backed by Danuser's 1-Year Manufacturer Warranty.

POST COMPATIBILITY

Post Type	Diameter / OD	Notes
T-Post	—	Standard application
Round Pipe	Up to 3" O.D.	Includes pipe, ground rod, or line post
Square Tube	Up to 3"	Ideal for fence corners or structural posts

USER OPERATION



Hydraulic system delivers consistent impact with minimal vibration.



Enclosed hammer design protects post tops from deformation.



Compatible with multiple quick-attach mounts for easy equipment integration.




Simple hydraulic connection enables quick setup across machines.

MAINTENANCE TIPS

- Inspect hydraulic fittings and couplers daily before operation.
- Check fluid levels and hoses for leaks or wear.
- Grease pivot points weekly for optimal performance.
- Store upright and covered to prevent debris accumulation.

Maintenance follows Danuser service guidelines.

Contact SONCO for pricing, compatibility guidance, and the right accessories for your next project.



BUILD YOUR FULL SETUP



T3 Skid-Steer Mount

Fits most skid steers and loaders; center or offset setup; includes post puller.



T3 Offset Mount

Extends up to 5 ft for parallel fence driving; includes hoses and safety markings.



T3 Mini-Skid Mount

Compact option with built-in puller for Toro, Vermeer, and Ditch Witch.



T3 John Deere Mount

For 200–500 series quick-attach; chain slot and built-in puller.



T3 Euro/Global Mount

For Euro/Global loaders; offset setup with integrated post puller.




T3 Bobcat MT Mount

Fits Bobcat MT skids; puller for fast install and removal.




Mount Bracket

Bolts or welds to a flat surface; connects the driver to mounting platforms.



Tilt Bracket

Tilts up to 20° left or right for accurate post alignment on uneven terrain.



Plumb Bob

Provides a hanging vertical reference for precise post placement.



Front-End Loader Hose Kit

25-ft hose with quick couplers; connects driver to hydraulic system.