

RHINO FENCE PRO™ GAS POST DRIVER

Built for demanding jobs, the Fence Pro™ delivers speed, precision, and durability for post-driven temporary fencing setups. Compact design for one-person operation.



Type: Gas-Powered Post Driver	Brand: Rhino Tool	Model Number: PDRFP
-------------------------------	-------------------	---------------------



TECHNICAL SPECIFICATIONS *(Provided by Rhino Tool)*

Engine	Honda™ GX35 4-Stroke
Engine Displacement	35.8 cc
Fuel Type	Gasoline [Unleaded 86 Octane or Higher]
Fuel Capacity	0.67 qt [0.63 L]
Engine Oil	SAE 10W-30
Lubricant	Rhino® Pro Series Grease
Beats Per Minute [BPM]	1,720 [Approximate]
Impact Energy	High-frequency impact suitable for round pipe and T-posts
Master Chuck I.D.	2.5" [63.5 mm]
Adapter System	Chuck-Lok™ Quick-Change System
Included Adapter	2" [50.8 mm]
Optional Adapters	1" [25.4 mm] and 1-3/4" [44.4 mm]
Compatible Post Sizes	Round Pipe up to 2-3/8" OD, T-Posts, Ground Rods, Concrete Pins
Construction	Heat-Treated Steel Components with Cast Aluminum Body
Vibration System	Rhino CIS™ Vibration Dampening
Driver Dimensions [L x W x H]	11" W x 14" D x 24" H [280 x 356 x 610 mm]
Total Product Weight	47 lbs [21.3 kg]
Driver Weight	37.8 lbs [17.1 kg]

WHY CHOOSE THIS MODEL?



Reliable performance for professional fence installations.



Supported by SONCO with nationwide stock.



U.S.-built, with Lifetime Impact Warranty and service managed by Rhino Tool.

POST COMPATIBILITY

Post Type	Diameter / OD	Required Adapter
T-Post	—	1-3/4" Adapter [Optional]
Ground Rod	1/2" – 3/4"	1" Adapter [Optional]
Concrete Form Pin	1"	1" Adapter [Optional]
Round Pipe	1" – 1-7/8"	2" Adapter [Included]
Round Pipe	1-3/4" – 2-3/8"	Standard Chuck [Included]

USER OPERATION



Designed for comfort and control with extended use.



CIS™ system reduces vibration and operator fatigue.



Runs independently without compressors or external power sources.

MAINTENANCE TIPS


- Apply Pro Series Grease every 10–15 hours of use.
- Change engine oil every 100 hours and check the air filter weekly.
- Inspect O-rings and seals at 300 hours or during service kit replacement.
- Clean spark plug and drain fuel before long-term storage.

Maintenance follows Rhino Tool service guidelines.

Contact SONCO for pricing, guidance, and the right accessories for your next project.




BUILD YOUR FULL SETUP



Post-Driven Fence Mesh
Chain-link fabric in 6x50 ft and 8x50 ft rolls.



Rack Bundle
Includes 20 mesh rolls with 8 ft or 10 ft posts for transport and storage.



Steel Posts
2" diameter, available in 8 ft or 10 ft heights.