

RHINO MULTI-PRO™ XA GAS POST DRIVER

Built for high-output jobsites, the Multi-Pro™ XA delivers extra power and reach for fast, consistent post installation.



Type: Gas-Powered Post Driver	Brand: Rhino Tool	Model Number: PDRMP
-------------------------------	-------------------	---------------------



WHY CHOOSE THIS MODEL?



Delivers greater impact energy and reach than standard gas drivers.



Reliable for large-scale temporary fencing and security setups.



Supported by SONCO with nationwide stock.



U.S.-built with Lifetime Impact Warranty and service managed by Rhino Tool.

TECHNICAL SPECIFICATIONS *[Provided by Rhino Tool]*

Engine	Honda™ GX35 4-Stroke
Fuel Type	Gasoline (Unleaded 86 Octane or Higher)
Fuel Capacity	0.67 qt [0.63 L]
Lubricant	Rhino® Pro Series Grease
Beats Per Minute [BPM]	1,720 [Approx.]
Impact Energy	High-frequency impact for pipe, posts & pins
Master Chuck I.D.	2.75" [69.85 mm]
Adapter System	Chuck-Lok™ Quick-Change System
Included Adapter	2.5" [63.5 mm] Chuck
Optional Adapters	1.75" [44.5 mm], 2" [50.8 mm], and 2.5" [63.5 mm] Adapters
Compatible Post Sizes	Round Pipe up to 3-1/8" OD, T-Posts, Ground Rods, and Form Pins
Construction	Heat-Treated Steel Components / Cast Aluminum Body
Handle System	Extended "XA" Handles with Padded Grips
Driver Dimensions [L x W x H]	11" x 14" x 32" [280 x 356 x 813 mm]
Driver Weight	41 lbs [18.6 kg]
Total Product Weight	52 lbs [23.6 kg] including accessories

POST COMPATIBILITY

Post Type	Diameter / OD	Required Adapter
T-Post	—	1.75" Adapter [Optional]
Ground Rod	1/2" – 3/4"	1" Adapter [Optional]
Concrete Form Pin	1"	1" Adapter [Optional]
Round Pipe	1-3/4" – 2-3/8"	2" Adapter [Optional]
Round Pipe	2-3/8" – 3-1/8"	2.5" Adapter [Included]

USER OPERATION



Extended handles improve grip and reduce operator fatigue.



CIS™ system reduces vibration and operator fatigue.



Runs independently without compressors or external power sources.

MAINTENANCE TIPS


- Apply **Pro Series Grease** after every 10–15 hours of use.
- Change engine oil every 100 hours and check the air filter weekly.
- Inspect O-rings and seals at 300 hours or during service kit replacement.
- Clean spark plug and drain fuel before long-term storage.

Maintenance follows Rhino Tool service guidelines.


Contact SONCO for pricing, guidance, and the right accessories for your next project.




BUILD YOUR FULL SETUP



Post-Driven Fence Mesh
Chain-link fabric in 6×50 ft and 8×50 ft rolls.



Rack Bundle
Includes 20 mesh rolls with 8 ft or 10 ft posts for transport and storage.



Steel Posts
2" diameter, available in 8 ft or 10 ft heights.